



MFN Series Modular Nugget Ice makers – up to 310kg MFN S 46 AS OX Nugget ice - 1g - Ø11mm x H 13mm



Nugget ice 1g -Ø11mm x H 13mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Maximum production rate 310kg/day
- Head only ice maker: requires a separate storage bin to store the ice produced
- XSafe Natural Sanitation System
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Air cooled version
- Hermetic compressor
- Stainless steel auger and freezing cylinder (evaporator)
- Plug-and-work technology
- Water in / ice out concept limits excess energy, water and time wastage
- Simple, reliable electromechanic controls
- External indicator lights to show operation status and maintenance alert
- Double protection electronic rotation sensor & drive coupling

- Low-water sensor protection
- Stainless steel finish, top cover in PS plastic with removable panels for ease of maintenance
- Includes removable air filter, water and drain hose

Recommended storage bins

- NB 193 with CBT 22 EFCD cover 129kg storage capacity
- NB 393 with CBT 30 EFSD cover 178kg storage capacity
- NB 530 with CBT 30 EFSD cover 243kg storage capacity
- NB 948 with CBT 48 FMCD cover 406kg storage capacity
- SIS 700 Ice shuttle storage system 318 + 73kg storage capacity






















MFN Series Modular Nugget Ice makers – up to 310kg

MFN S 46 AS OX







 \oplus

 \oplus

 \oplus

Ф



Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia


Telephone 03-9518 3888 vsales@moffat.com.au

Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone 08-9413 2400 wasales@moffat.com.au



UNIT OF MEASUREMENT: mm

- 1. 7/8" WATER OUTLET
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET

32°C / 21°C

220

Refrigerant type R404a

Installation distance from wall 100mm Rear

Side 150mm Operating requirement air temperature 10-43°C

350

201

Dimensions

21°C / 10°C

310

Ambient temperature / Water temperature

Width: 538mm 663mm Depth: 645mm Height: Nett weight: 78kg Packed weight:

Ice production per 24 hours

Water consumption

10°C / 10°C

320

Air cooled version: 10 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 1200W,

10A cordset supplied

No. Circuit wire: 3304W Compressor: Energy consumption: 28kW/24hr

Water connection requirements

Inlet connection: R 3/4' 5-38°C Cold water: 100-500kPa Pressure: Water outlet connection: Ø7/8"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd