



TECHNICAL INFORMATION

| | |
|-------------------------|---------------------|
| Dimensions | 735w x 750d x 2465h |
| Rack Dimension | 500 x 600 |
| Clear Entry Height | 560 |
| Rinse Water Consumption | 2.2L Per Cycle |

WATER CONNECTIONS

| | |
|-----------------------|-----------------|
| Connection Point | 3/4 inch (19mm) |
| Inlet Temperature | 20c Max |
| Flow Rate | 4 L/Min |
| Flow Pressure | 1.5 bar/Min |
| Wastewater Connection | 23.6mm |

ELECTRICAL

| | |
|--------------------|-----------------------------------|
| 3 Phase (Standard) | 415v 3P 50Hz - 20amp (TCL 9.7Kw) |
| 3 Phase (Optional) | 415v 3P 50Hz - 25amp (TCL 11.5Kw) |
| 3 Phase (Optional) | 415v 3P 50Hz - 32amp (TCL 15.7Kw) |

GENERAL DATA

| | |
|--------------------|---------------------------------|
| Weight (Net/Gross) | 148/167Kg |
| Tank Capacity | 35L |
| Noise Emission | 62dB(A) |
| Cycle Times | 80/110/140 Seconds (Adjustable) |

STANDARD INCLUSIONS

| |
|--|
| 1x 3phase Lead |
| 1x 1m Flexible Water Connection Hose |
| 1x 1m Flexible Waste Hose |
| 2x 500 x 600 Racks (1x Flat, 1x Plate) |

OPTIONS

| |
|--|
| Automatic Hood: Automatic opening and closing of the hood by press of a button |
| Driven Rinse System to reduce the rinse water volume |

STANDARD FEATURES

- Smart touch display: simple single button operation
- Top & bottom S shaped washfields
- Variopower washing pressure adjustment
- Chemical pumps
- Rinse booster pump
- Drain pump
- Active energy management
- EnergyLight: waste water heat recovery system
- Quadruple filtration
- Clouding sensor
- Connected wash
- Timer for automatic start up and close down
- Hood start: washing program starts by closing the hood
- Exhaust air heat recovery reduces steam and energy costs

CERTIFICATES

WRAS
Watermark Approval
Hygiene Certificate according to DIN 10534