



PRODUCT ADVANTAGES

- Electronic control with digital temperature indication and 3 programmes for easy operation.
- GENIUS-X fine filter system: ensures the best wash result and saves energy and detergent costs.
- CLIP-IN wash and rinse arms: wash and rinse arms can be removed without any tools.
- Thermostop function: automatic cycle time control to achieve hygienic rinsing temperatures.
- Double-walled housing: the machine is double-walled, soundproof and heat-insulated.
- Smooth counterbalanced door: soft, silent opening and closing. The dishwasher doors have gas-filled shock absorbers to protect your tableware and prevent wear of the door suspension.
- Optional refill signal: monitors contents of external chemical containers at any time. The control indicates well in advance when detergent and rinse aid need refilling.
- Optional 2IN1 double rack system: two racks can be washed in a single wash cycle. Thanks to the optimum use of the entire wash chamber, the performance of the machine can be doubled.
- Thermolabel 71 °C: default temperatures setting acc. European DIN can be switched by operator to a higher thermolabile setting.
- Watermark approved
- Made in Germany

TECHNICAL DATA

Cycle times*	90 / 180 / 360 sec. and self-cleaning programme
Water consumption	2.0 l/rack
Tank capacity	10.6 l
Tank heating	1.7 kW
Power supply	240 / 50 / 1 (415 / 50 / 3N)
Booster loading	
Standard	2.1 kW
Alternative	6.2 kW
Total loading	
Standard	2.7 kW 15 A
Alternative	6.8 kW 3 x 15 A
Wash pump	0.5 kW
Rack size	500 x 500 500 x 530 mm
Loading height	425 mm
Noise level	59 dB (A)
Weight (gross/net)	70 / 60 kg

* The machine is equipped with an automatic programme time extension which ensures hygienic rinse temperatures, even on a cold-water supply or 240 V connection.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water softener of the product line HYDROLINE PROTECT.

To avoid spots and streaks on the wash ware, we recommend the usage of a demineralisation cartridge (HYDROLINE STAR / STAR EXTRA) or a reverse osmosis system HYDROLINE PURE (please refer to HOBART Export price list 2022, chapter 1.6).

CONNECTIONS

(1) Drain hose	2,000 mm ID20 / AD25
(2) Supply hose	2,000 mm R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 - 10 (with softener: 0.8 - 10) bar
Max. supply temperature	60 °C
(3) Connection cable	2,000 mm
Supply hose for	
(4) Detergent	2,500 mm
(5) Rinse aid	2,500 mm

DRAWING

