



TECHNICAL INFORMATION

| | |
|-------------------------|------------------------------|
| Dimensions | 600 mm x 600 mm x 820/850 mm |
| Rack Dimension | 500 x 500 mm |
| Clear Entry Height | 352 mm |
| Rinse Water Consumption | 2.1L - 2.75L |

WATER CONNECTIONS

| | |
|-------------------|------------------|
| Connection Point | G3/4" (3/4" BSP) |
| Inlet Temperature | 20 - 55°C |
| Flow Rate | 4 L/Min |
| Flow Pressure | 1-10 bar |
| Drain Size | 40mm |
| Waste Height | 600mm |

ELECTRICAL

| | |
|-------------------------|-----------|
| Single Phase (Standard) | 15A - 30A |
| 3 Phase (Optional) | 15A |
| Power Consumption | 6.58Kw |

GENERAL DATA

| | |
|---------------------|--|
| Weight (Net/Gross) | 52Kg (60Kg) |
| Wash Tank Capacity | 15 L |
| Rinse Tank Capacity | 6.5L |
| Noise Emission | <70 (dB) |
| Cycle Times | 1.5 & 2 min Glass / 2 , 3 & 5 min Dish |

STANDARD INCLUSIONS

Glass, dish & cutlery racks

STANDARD FEATURES

- Energy-saving standby mode
- Drain pump
- Rinse booster pump
- Detergent, and rinse pumps
- Colour-coded display
- Reduced rinse water consumption
- Double-skinned door and cabinet to reduce noise and limit heat loss
- Hygiene and service reminders
- Deep clean mode and refresh cycle
- Optional audible alarm
- Three power options:
 - 15A Single Phase
 - 30A Single Phase
 - 15A Three Phase